

CPR Model - Round Shape Panel Mount Thermocouple Connectors -29 to 220 deg C



Socket mounting

- Types, K, J, T, E, N U available
- Material : Glass Filled Nylon
- Temperature : -29°C to 220°C
- Square or Round shape or Panel Mount Metal Bracket
- Standard accepts all industry standard Size connectors
- Miniature accepts all industry miniature connectors.
- Colour-Coded for ANSI
- Polarity Keyed
- Combination Philips / Slots screw

Panel Mount Connector – CPR (Round)						
Calibration	Colour	Colour Code Ansi	Alloy		Panel Cutout Size mm	Miniature socket
			+VE	-VE		
K	Yellow	Yellow	Chromel	Alumel	Ø16	CPR002-K
J	BLACK	Black	Iron	Constantan	Ø16	CPR002-J
T	BLUE	Blue	Copper	Constantan	Ø16	CPR002-T
E	PURPLE	Purple	Chromel	Constantan	Ø16	CPR002-E
N	ORANGE	Orange	Chromel	Constantan	Ø16	CPR002-N
R/S	GREEN	Green	Copper	RNX/SNX	Ø16	CPR002-RS
U	WHITE	White	Copper	Copper	Ø16	CPR002-U
Calibration	Colour	Colour Code Ansi	Alloy		Panel Cutout Size mm	Standard socket
			+VE	-VE		
K	Yellow	Yellow	Chromel	Alumel	Ø22.4	CPRS002-K
J	BLACK	Black	Iron	Constantan	Ø22.4	CPRS002-J
T	BLUE	Blue	Copper	Constantan	Ø22.4	CPRS002-T
E	PURPLE	Purple	Chromel	Constantan	Ø22.4	CPRS002-E
N	ORANGE	Orange	Chromel	Constantan	Ø22.4	CPRS002-N
R/S	GREEN	Green	Copper	RNX/SNX	Ø22.4	CPRS002-RS
U	WHITE	White	Copper	Copper	Ø22.4	CPRS002-U