

HH Series - Temperature Sensor for Thermometer

HH Series is a general purpose handheld portable probe sensor available in Type K or PT100. The sensor come with a handle, coil wire and miniature plug. Coil wire is 250mm with extension of 1.5 meter PVC/PVC length. The handheld sensor is suitable to be used in all kinds of Type K or PT100 Thermometer with type K or PT100 miniature plug connector connection.

Hand Held General Purpose Sensor Order Code: HH100K for K sensor

Order Code: HH100PT for PT100 sensor

Order Code	Type
HH100K	K
HH100PT	PT100

✓ Type Available: Type K or PT100 – 3 Wire

✓ It is offered to measure air and liquid

✓ Overall Probe length: 200 mm

✓ Max Temperature rated : 400 °C for K sensor

✓ Max Temperature rated : 200 °C for PT100 sensor

		1
	A	
-		MALES HUMBURGON

Order Code	Type
HH101K	K
HH101PT	PT100



Hand Held General Purpose Spear Point Sensor HH101K for K sensor / HH101PT for PT100 sensor


- ✓ Type Available: Type K, PT100 3 wire
- It is offered to measure air and liquid
- Overall Probe length: 200 mm
- ✓ Max Temperature rated : 400 °C for K Sensor
- ✓ Max Temperature rated : 200°C for PT100 Sensor

Hand Held Air Temperature Sensor HH102K for K sensor HH102PT for PT100 sensor

- ✓ Type Available: Type K, PT100 3 Wire
- ✓ It is offered to measure air
- ✓ Overall Probe length : 200 mm
- ✓ Max Temperature rated : 400 °C for K sensor
- ✓ Max Temperature rated : 200 °C for PT100 sensor

Order Code	Type
HH102K	K
HH102PT	PT100





Hand Held Quick Respond Right Angle Spring Loaded Surface Sensor HH103K

- ✓ Type Available: Type K
- ✓ It is offered to measure surface temperature and it is positioned at right angle for difficult to reach application.
- ✓ Overall Probe length : 200 mm
- ✓ Max Temperature rated: 400 ° C



HH1-16-01

HH Series - Temperature Sensor for Thermometer

Hand Held Quick Respond Spring Loaded Surface Sensor HH104K

- ✓ Type Available: Type K
- ✓ It is offered to measure surface temperature such as bearing housing, motoring etc
- ✓ Overall Probe length : 200 mm
- ✓ Max Temperature rated: 400 ° C

Order Code	Type
HH104K	K





Hand Held Quick Respond Spring Loaded Surface Roller Sensor HH105K

- ✓ Type Available: Type K
- ✓ It is offered to measure surface temperature such as slow movable belt, machinery etc
- ✓ Roller is made of Teflon material
- ✓ Max Temperature rated: 200 ° C

Order Code	Type
HH105K	K



Quick Respond Spot Weld Thermocouple

- ✓ Type K
- ✓ Conforms to ASTM E230,
- ✓ IEC 584 and Ansi MC96.1
- ✓ Temperature rated: -40 to 200 ° C
- ✓ Wire Length: 1 mtr Teflon
- ✓ Wire Insulation rated : -200 to 200°C
- ✓ Wire Size : 1/0.254

Order Code	Туре
HH106K	K
HH107K	K