

**JUST POWER UP  
CONVENIENT  
READY TO USE !**

# PCM

## Portable Bench Top Temperature Controller / Display

### Feature

- Display size : 24 x 48mm, 48x48mm available
- Input : T/C - K, J, T, PT100, PT1000
- Output: Relay , SSR
- Miniature female socket for sensor connection
- Power switch for on/off
- Power cord included – 240 VAC
- Portable
- Probe sensor - optional



**P01 - Probe Sensor (optional) – ready to use**  
Dia : 5 x 50 mm  
Wire Length : 1 mtr Teflon/Teflon

Order Code	Type	Display Size (mm)	INPUT	OUTPUT
PCM1-R- <b>X</b>	w/o sensor	24 x 48	K/J/T/PT100	RELAY
PCM1-S- <b>X</b>	w/o sensor	24 x 48	K/J/T/PT100	SSR
PCM1-R-P01- <b>X</b>	c/w sensor P01	24 x 48	K/J/T/PT100	RELAY
PCM1-S-P01- <b>X</b>	c/w sensor P01	24 x 48	K/J/T/PT100	SSR

Indicate input type K, J, T or PT100 as highlighted in red 'X'

Order Code	Type	Display Size (mm)	INPUT	OUTPUT
PCM2-R- <b>X</b>	w/o sensor	48 x 48	K/J/T/PT100	RELAY
PCM2-S- <b>X</b>	w/o sensor	48 x 48	K/J/T/PT100	SSR
PCM2-R-PT1000	w/o sensor	48 x 48	PT1000	RELAY
PCM2-S-PT1000	w/o sensor	48 x 48	PT1000	SSR
PCM2-R-P01- <b>X</b>	c/w sensor P01	48 x 48	K/J/T/PT100	RELAY
PCM2-S-P01- <b>X</b>	c/w sensor P01	48 x 48	K/J/T/PT100	SSR

Indicate input type K, J, T or PT100 as highlighted in red 'X'

Order Code	Type	Display Size (mm)	INPUT	OUTPUT
PCM3-R- <b>X</b>	w/o sensor	96 x 96	K/J/T/PT100	RELAY
PCM3-S- <b>X</b>	w/o sensor	96 x 96	K/J/T/PT100	SSR
PCM3-R-P01- <b>X</b>	c/w sensor P01	96 x 96	K/J/T/PT100	RELAY
PCM3-S-P01- <b>X</b>	c/w sensor P01	96 x 96	K/J/T/PT100	SSR

Indicate input type K, J, T or PT100 as highlighted in red 'X'