

PTM

Portable Bench Top Temperature Controller with Timer

JUST POWER UP
CONVENIENT
READY TO USE !



Feature

- Display size : 24 x 48mm, 48x48mm, 96x96mm available
- Input : T/C - K, J, T, PT100
- Output: Relay , SSR
- Miniature female socket for sensor connection
- Power switch for on/off
- Power cord included – 240 VAC
- Portable
- Probe sensor - optional
- Programmable timer for timing control

P01 - Probe Sensor (optional) – ready to use
Dia : 5 x 50 mm
Wire Length : 1 mtr Teflon/Teflon with Miniature plug

Order Code	Order Code With Probe sensor	Display Size (mm)	INPUT	OUTPUT
PTM1-R- X	w/o sensor	24 x 48	K/J/T/100	RELAY
PTM1-S- X	w/o sensor	24 x 48	K/J/T/100	SSR
PTM1-R- X -P01	c/w sensor P01	24 x 48	K/J/T/100	RELAY
PTM1-S- X -P01	c/w sensor P01	24 x 48	K/J/T/100	SSR

Indicate input type K, J, T or PT100 as highlighted in red 'X'

Order Code	Order Code With Probe sensor	Display Size (mm)	INPUT	OUTPUT
PTM2-R- X	w/o sensor	48 x 48	K/J/T/100	RELAY
PTM2-S- X	w/o sensor	48 x 48	K/J/T/100	SSR
PTM2-R- X -P01	c/w sensor P01	48 x 48	K/J/T/100	RELAY
PTM2-S- X -P01	c/w sensor P01	48 x 48	K/J/T/100	SSR

Indicate input type K, J, T or PT100 as highlighted in red 'X'

Order Code	Order Code With Probe sensor	Display Size (mm)	INPUT	OUTPUT
PTM3-R- X	w/o sensor	96 x 96	K/J/T/100	RELAY
PTM3-S- X	w/o sensor	96 x 96	K/J/T/100	SSR
PTM3-R- X -P01	c/w sensor P01	96 x 96	K/J/T/100	RELAY
PTM3-S- X -P01	c/w sensor P01	96 x 96	K/J/T/100	SSR

Indicate input type K, J, T or PT100 as highlighted in red 'X'