


QUADVOLT 4 CHANNEL VOLTAGE DATA LOGGER

Features

- Real-time operation
- Programmable engineering units
- Low cost
- Reusable
- Compact
- User-friendly
- Programmable start time

Applications

- Low level signal monitoring
- Medical and pharmaceutical
- Battery studies
- Power supply monitoring
- Process plants
- Environmental studies
- Research and development
- Replace costly strip chart recorders




The Quadvolt is a four channel, battery powered, stand-alone voltage recorder. This is an all-in-one compact, portable, easy to use device that will measure and record up to 32,767 measurements per channel. The storage medium is non-volatile solid state memory, providing maximum data security even if the battery becomes discharged. The device can be started and stopped directly from your computer and its small size allows it to fit almost anywhere. The QuadVolt makes data retrieval quick and easy. Simply plug it into an empty COM or USB port and our user-friendly software does the rest.

MADGETECH DATA LOGGER SOFTWARE

Key

- Graph View
- Tabular Data View
- Statistics
- Digital Calibration
- Copy to Excel®



Software Features:

- Multiple graph overlay
- Statistics
- Digital calibration
- Zoom in/ zoom out
- Lethality equations (F0, PU)
- Mean Kinetic Temperature
- Full time zone support
- Data annotation
- Min./Max./Average lines
- Data table view
- Automatic report generation
- Summary view
- Multilingual

QUADVOLT SPECIFICATIONS*

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. SPECIFIC WARRANTY REMEDY LIMITATIONS APPLY.

Input Connection:	4 removable screw terminals		
Model:	2.5 V	15 V	30 V
Voltage Range:	-0.25 to +2.75	-1.0 to +16.0	-2.0 to +32.0
Voltage Resolution:	0.1 mV	0.5 mV	1.0 mV
Calibrated Accuracy:	±0.01 (%FSR)	±0.10 (%FSR)	±0.10 (%FSR)
Input Impedance:	>1 kΩ*	>10 kΩ	>10 kΩ
Overload Protection:	±5 V	±30 V	± 48 V
Temperature Coefficient:	< 25 ppm/°C	< 250 ppm/°C	< 250 ppm/°C
Analog Conversion Time:	133 ms		
Frequency Rejection:	60 Hz		
Specified Accuracy Range:	Nominal range @ 25 °C		
Engineering Units:	User may define units up to 10 characters in length. This value is stored within the device.		
Scale Factor:	User may program any desired scaling factor from ±1.000E-31 to ±9.999E+31. The scaling factor is stored within the device.		
Start Modes:	Software programmable immediate start or delay start up to six months in advance		
*Input impedance is greater than 1 MΩ during acquisition for the QUADVOLT-2.5			

Memory:	32,767 readings per channel; 131,068 total readings
Reading Rate:	1 reading every second up to 1 reading every 12 hours
Real Time Recording:	May be used with PC to monitor and record data in real time
Calibration:	Digital calibration through software
Calibration Date:	Automatically recorded within device
Battery Type:	9V lithium or alkaline battery included; user replaceable
Battery Life:	1 year typical
Data Format:	Date and time stamped V, mV, μV, engineering units specified through software
Time Accuracy:	±1 minute/month (at 20 °C, RS232 cable not in use)
Computer Interface:	PC serial or USB (interface cable required); 2,400 baud
Software:	XP SP3/Vista/Windows 7/Windows 8
Operating Environment:	-20 °C to +60 °C, 0 %RH to 95 %RH non-condensing
Dimensions:	3.5 in x 4.4 in x 1.0 in (89 mm x 111 mm x 26 mm)
Weight:	13 oz (370 g)

BATTERY WARNING: DISCARD USED BATTERY PROMPTLY. KEEP OUT OF REACH OF CHILDREN. DO NOT DISPOSE OF IN FIRE, RECHARGE, PUT IN BACKWARDS, DISASSEMBLE, OR MIX WITH OTHER BATTERY TYPES. MAY EXPLODE, FLAME OR LEAK AND CAUSE PERSONAL INJURY.

ORDERING INFORMATION

MODEL	DESCRIPTION
QUADVOLT-100mV	±100mV 4 Channel Voltage Recorder
QUADVOLT-2.5V	±2.5V 4 Channel Voltage Recorder
QUADVOLT-15V	±15V 4 Channel Voltage Recorder
QUADVOLT-30V	±30V 4 Channel Voltage Recorder
IFC110	Software, manual and RS232 interface cable
IFC200	Software, manual and USB interface cable
NIST	NIST Calibration Certificate
U9VL-J	Replacement battery for QuadVolt

ASK ABOUT
OUR OTHER
DATA
LOGGERS

Temperature

Humidity

Pressure

pH

Level

Shock

LCD Display

Pulse/Event/State

Current

Voltage Wireless

Intrinsically Safe

Spectral Vibration

Motion