

ORDERING CODE

FSE Model

FSE - [1] [2] [3] - [4] [5] - [6] [7] - [8] [9] - [10] [11] - [12] [13]

Eg 1: FSE Model, Four Float – 2 Wire per float, Material: SS316, Standard Head Enclosure D2, Float Dia: Ø28, Activation Length L1 = 100mm, L2=250mm, L3= 400mm, L4=700mm, Switch Configuration (F1=H, F2=L, F3=H, F4=L)
Order Code : FSE-S4D2-2WD28-100H-250L-400H-700L

Eg 2: FSE Model, Four Float – 3 Wire per float (NC, NO, Common), Material: SS316, Standard Head Enclosure D2, Float Diameter : Ø45, Activation Length L1 = 100mm, L2=250mm, L3= 400mm, L4=700mm
Order Code : FSE-S4D2-3WD45-100N-250N-400N-700N

1 FLOAT SENSOR MATERIAL
S: SS316

2. NUMBER OF FLOAT
1: 1 Float Ball 3: 3 Float Ball
2 : 2 Float Ball 4: 4 Float Ball

3 HEAD ENCLOSURE DESIGN (See Accessories section for Enclosure design)
D2: Standard Alloy Aluminum X1: Xproof Alloy Aluminum
D8: Standard Cast Stainless Steel X2: Xproof Stainless Steel
D13: Alloy Aluminum Rectangular X4: XLarge G2D4 Xproof Aluminum

4 Number of Wire per Float ball
2W: 2 Wire – (Need specify Switch configuration for 2 wire per float ball)
3W: 3 Wire (NC, NO, Common) - (Do not need to specify Switch configuration, indicate '0': Nil)

5 FLOAT SIZE (Ø)
Stainless steel SS316 material
D28 : Ø28 x H28mm D75 : Ø75 x H75mm
D38 : Ø38 x H26.5mm D76 : Ø76 x H100mm
D45 : Ø45 x H56mm D125 : Ø125 x H125mm
D50 : Ø51 x H61mm

6 ACTIVATION LENGTH L1 (Specify length accordingly)
150 : 150mm 350 : 350mm
250: 250mm 450: 450mm

7 SWITCH CONFIGURATION (F1)
N: NIL (For 3 Wire per float)
L: NO, NC H: NC, NO

8 ACTIVATION LENGTH (L2) (Specify length accordingly)
N: Nil 200 : 200mm
150 : 150mm 350 : 350mm

9 SWITCH CONFIGURATION (F2)
N: NIL
L: NO, NC H: NC, NO

10 ACTIVATION LENGTH (L3) (Specify length accordingly)
N: Nil 200 : 200mm
150 : 150mm 350 : 350mm

11 SWITCH CONFIGURATION (F3)
N: NIL
L: NO, NC H: NC, NO

12 ACTIVATION LENGTH (L4) (Specify length accordingly)
N: Nil 200 : 200mm
150 : 150mm 350 : 350mm

13 SWITCH CONFIGURATION (F4)
N: NIL
L: NO, NC H: NC, NO

Remarks: Not all combinations are available however we will offer the nearest to your requirement

